ALZW26A



Product

Take-A-Number PRO system, sd card

Description:

This waiting line management package includes a hard-wired buttons and Take-a-number PRO controller with SD Card Memory for capturing wait times, number of people waiting and a host of other events and a three-digit Display with 5" high digits. This system may also be expanded to serve up to six different services at multiple windows. One indicator is placed over each respective window.

Item: ALZW26A

UPC: 788581657386

EAN: 0788581657386

Dimensions: 52.0" x 16.0" x 16.0"

Weight: 29.84 lbs. **MSRP:** \$3,940.50

Specifications:

- Two RJ45 modular connectors for RS422 serial data transmission and reception.
- Two RJ11 modular connectors for accessories.
- RJ11 modular connector for remote button inputs.
- Power connector (2.1x5.5mm).
- Test button for testing and configuration.
- Power requirements: 10-15VAC or 12-20VDC.
- Current consumption: 100mA maximum per digit.
- Construction: Metal enclosure, black powder coated finish with transparent red acrylic front.
- DC117B6 WAIT1 Dimensions: 6.4" x 3.7" x 2.5".

Features:

- Convenience is important to most people. This gives you an advantage as Alzatex timers are easy to use. The real benefit to you is a very quick learning curve.
- Five-Digit 5" LED display showing Now Serving ticket number.
- Standard mounting is 2 key hole slots spaced 9 inches apart for wall mounting.
- There are screws at either end of the displays where D-Rings can be added. D-Rings are NOT included and may be ordered separately.
- There is one 1/4-20 nut on the bottom of the unit for attaching camera style tripod.
- Includes Take-A-Turn ticket printer with one request service (ticket print) button.
- Two push buttons can be installed for multiple windows.

Item Includes:

- (1) DSP505B-NSW Large LED Display.
- (2) PB1-WH White Push Button.
- (2) NL16AG Indicator Lamp.
- (1) RLY15A-GC Ground Closure Module.
- (1) PR121C1 TAT Ticket Printer.
- (1) PR921A1R Thermal Printer Paper (1 Roll).
- (1) DC117B6-WAIT1 TAT Printer Controller.
- (1) KTP7X422A-8B Button Input Module.
- (1) M2C22G050F 50ft, 22ga, 2-conductor wire.
- (3) M8BK050F 50ft, Cat-5, 8-conductor cable.
- (2) M8BK003F 3ft, Cat-5, 8-conductor Cable.
- (1) PSYM04-120 Power Supply, 12VDC, 9A.
- (1) RC Reference card.
- (1) WD Wiring diagram.



